



Full Colour Photocopier - Document Management

# Colour Manager

- Accelerated productivity for your office, that keeps pace with your output demands.
- Breathtaking colour and clarity due to superior image quality.
- Unsurpassed ease-of-use allows optimal multifunction operations.
- Ready for integration, ready for your office.

- e-STUDIO2330c**
- e-STUDIO2820c**
- e-STUDIO3520c**
- e-STUDIO4520c**





**e-STUDIO2330c**  
**e-STUDIO2820c**  
**e-STUDIO3520c**  
**e-STUDIO4520c**



<p><b>General</b></p>	<p><b>Print &amp; Copy Speed</b> Colour: 23/28/35/45 ppm (A4), 12/16/18/22 ppm (A3)          B&amp;W: 28/28/35/45 ppm (A4), 16/16/18/22 ppm (A3)</p> <p><b>Warm-up Time</b> Approx. 30 seconds from low-power mode</p> <p><b>Paper Size &amp; Weight</b> Cassettes: A5R-A3, 64-256 gsm          Bypass: A6R-320 x 460 mm, 64-280 gsm, banner paper (305 x 1,200 mm), 64-163 gsm</p> <p><b>Paper Capacity</b> 2 x 550 sheets (Cassettes), 100 sheets (Bypass)          Maximum: 3,700</p> <p><b>Automatic Duplex Controller Type</b> Up to A3+ and 256 gsm</p> <p><b>Memory</b> Toshiba e-BRIDGE</p> <p><b>Interface</b> 80 GB HDD, 1.5 GB RAM</p> <p><b>Dimensions &amp; Weight</b> 10/100BaseT (incl. IPv6), High-Speed USB 2.0, WLAN<sup>1)</sup> (IEEE802.11b/g), Bluetooth<sup>1)</sup>          699 x 774 x 759 mm (W x D x H), approx. 121 kg</p>
<p><b>Print</b></p>	<p><b>Resolution</b> Max. 600 x 600 dpi, 8 bit per channel</p> <p><b>Page Description Language</b> XPS, PCL6 and PostScript 3 compatible</p> <p><b>Supported Systems</b> Windows 2000, Windows XP/Server2003/Server 2008/Vista (32/64 bit), Mac OS X, Linux/UNIX, Novel Netware (NDPS), Citrix, SAP, AS/400</p> <p><b>Colour Modes</b> Auto-Colour (ACS), Colour, Grayscale, B&amp;W</p> <p><b>Colour Settings</b> Brightness, Saturation, Contrast, Colour Balance</p>
<p><b>Scan</b></p>	<p><b>Resolution</b> Max. 600 x 600 dpi, 8 bit per channel</p> <p><b>Scan Speed</b> Colour &amp; B&amp;W: Up to 57 pages/min. (300 dpi)</p> <p><b>Document Feeder<sup>1)</sup></b> Max. 100 sheets, A5R-A3, 35-157 gsm</p> <p><b>Scan Modes</b> Auto-Colour (ACS), Colour, Grayscale, B&amp;W</p> <p><b>File Formats</b> JPEG, Multi/Single Page TIFF, Multi/Single Page XPS, Multi/Single Page PDF, Secure PDF, Slim PDF (high compression), Searchable PDF<sup>1)</sup> (and other editable formats like DOC, XLS, RTF, TXT)<sup>1)</sup></p> <p><b>Scan Functions</b> WS Scan (pull/push), Scan to USB, Scan to E-Mail, Scan to File (SMB, FTP), Meta Scan<sup>1)</sup>, Scan to Box (e-Filing), TWAIN 1.7</p>
<p><b>Copy</b></p>	<p><b>Resolution</b> Scanning: 600 x 600 dpi, 10 bit per channel          Printing: 600 x 600 dpi, 8 bit per channel</p> <p><b>First Copy</b> 2,400 x 600 dpi, B&amp;W with smoothing</p> <p><b>Zoom</b> Colour: Approx. 8.4/8.4/8.4/6.8 seconds</p> <p><b>Copy Modes</b> B&amp;W: Approx. 6.5/6.5/6.5/5.2 seconds</p> <p><b>Colour Modes</b> 25-400% (platen glass), 25-200% (RADF)<sup>1)</sup></p> <p><b>Colour Settings</b> Text, Text/Photo, Photo, Printed Image, Map Auto-Colour (ACS), Full Colour, Twin Colour, Mono Colour, B&amp;W          Hue, Saturation, Colour Balance, 5 One-touch Modes, RGB Adjustment</p>
<p><b>Fax<sup>1)</sup></b></p>	<p><b>Communication</b> Super G3, G3 - (opt. 2<sup>nd</sup> line), Internet Fax T.37</p> <p><b>Transmission Speed</b> Approx. 3 seconds per page</p> <p><b>Compression</b> JBIG, MMR, MR, MH</p> <p><b>Network-Fax</b> Driver for Windows 2000/XP/Vista (32/64 bit)</p> <p><b>Incoming Fax Routing</b> To shared folder (SMB, FTP), e-mail, e-Filing</p>
<p><b>System &amp; Security</b></p>	<p><b>Device Management</b> e-BRIDGE Fleet Management Software<sup>1)</sup>, TopAccess remote administration &amp; configuration</p> <p><b>System Features</b> e-Filing document server for secure storage, document distribution and Print on Demand (1 public box, 200 user boxes), 12,060 One-touch Templates for storage of personalised settings or workflows, Scan preview, Print from USB, e-BRIDGE Open Platform<sup>1)</sup></p> <p><b>Accounting &amp; Security</b> Role Based Access, LDAP support, 1,000 department codes &amp; 10,000 user codes, card reader support, private print, standard data encryption, Data Overwrite Enabler<sup>1)</sup>, IP and MAC address filter, port filter, support of SSL and IPsec<sup>1)</sup> protocol, IEEE802.1x support, Scan to secure PDF</p>

Productivity and paper specifications are related to a paper size of A4 and a paper weight of 80 gsm if not otherwise mentioned.

**OPTIONS**

**RADF – MR-3018**

100 sheet capacity, A5R-A3, 35-157 gsm

**MULTI-STAPLE FINISHER – MJ-1101**

2 trays, 2,250 sheet capacity  
 50 sheet multi-position staple  
 A5R-A3, 64-105 gsm (staple mode)  
 535 x 598 x 1,092 mm (W x D x H), ~ 34 kg

**SADDLE-STITCH FINISHER – MJ-1030**

2 trays, 2,000 sheet capacity  
 50 sheet multi-position stapling  
 Saddle-stitched booklets of up to 60 pages  
 A5R-A3, 64-105 gsm (staple mode)  
 649 x 657 x 1,086 mm (W x D x H), ~ 70 kg

**HANGING FINISHER – MJ-1031**

1 tray, 1,000 sheet capacity  
 50 sheet single position stapling  
 A5R-A3, 64-105 gsm (staple mode)  
 411 x 595 x 383 mm (W x D x H), ~ 12 kg

**HOLE PUNCH UNIT – MJ-6004 / MJ-6101**

Option for Finisher MJ-1030/MJ-1101  
 Available in 2-holes (E), 4-holes (F),  
 112 x 617 x 378 mm (W x D x H), ~ 9 kg  
 112 x 573 x 323 mm (W x D x H), ~ 7 kg

**PAPER FEED PEDESTAL – KD-1023**

550 sheet (1 drawer), A5R-A3, 64-256 gsm  
 623 x 643 x 320 (W x D x H), ~ 21 kg

**LARGE CAPACITY FEEDER – KD-1024A4**

2,500 sheet capacity, A4, 64-105 gsm  
 623 x 643 x 308 mm (W x D x H), ~ 27 kg

**OTHER OPTIONS**

- DESK MH-1700
- DRAWER MODULE MY-1032
- FAX BOARD GD-1250EU
- DATA OVERWRITE ENabler GP-1070
- E-BRIDGE ID-GATE KP-2004/KP-2005
- IMAGING ACCELERATION BOARD GE-1170
- WIRELESS LAN ADAPTER GN-1050
- BLUETOOTH ADAPTER GN-2010
- META SCAN ENabler GS-1010
- WEB-SERVICES ENabler GS-1020
- IP SEC ENabler GP-1080
- 2nd LINE FOR FAX UNIT GD-1260

<sup>1)</sup> Optional



Technical data is subject to change without prior notice. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries. All rights reserved. We are constantly making efforts to deliver the latest status of data to our partners. Specifications for some models may change in the time between the production and the release of this documentation. Copyright © 2007 TOSHIBA TEC. DS4-620CGB0807

**TOSHIBA TEC UK  
 IMAGING SYSTEMS LTD**

ABBAY CLOISTERS, ABBAY GREEN,  
 CHERTSEY, SURREY, KT16 8RB.  
 TEL 01932 580100 FAX 01932 580101  
 WWW.TOSHIBA.CO.UK/IMAGING